

MATERIAL SAFETY DATA SHEET (MSDS)

Cal-CM Plus Standard Prilled Calcium Sulfate

SECTION I	IDENTITY (As used on label and list)
------------------	---

Manufacturing Facility:

ART WILSON CO.

PO BOX 20160

CARSON CITY, NV 89721-0160

CAL-CM PLUS

STANDARD PRILLED CALCIUM SULFATE

SECTION II	HAZARDOUS INGREDIENTS / IDENTITY INFORMATION
-------------------	---

Hazardous components (specific chemical identity, common names OSHA PEL / ACGIH TLV / other limits recommended % optional)

NONE

SECTION III	PHYSICAL / CHEMICAL CHARACTERISTICS
--------------------	--

Boiling Point

NONE

Bulk Density(pounds/cubic foot)

69-76

Vapor Pressure (mm Hg)

NONE

Melting Point

1,450° C

Vapor Density Air =1)

NONE

Evaporation Rate (Butyl Acetate = 1)

NONE

Solubility in Water

0.2%

Appearance and Odor

SECTION IV	FIRE AND EXPLOSION HAZARD DATA
-------------------	---------------------------------------

Flash Point (method used)

NON-FLAMMABLE

SECTION V	REACTIVITY DATA
------------------	------------------------

Stability

STABLE

Conditions to Avoid

NONE

Incompatibility (materials to avoid)

ACIDS

Hazardous Decomposition or By-Products

NONE

Hazardous Polymerization

WILL NOT OCCUR

Conditions to Avoid

NONE

SECTION VI	HEALTH HAZARD DATA
-------------------	---------------------------

NON-HAZARDOUS

SECTION VII	PRECAUTIONS FOR SAFE HANDLING AND USE
--------------------	--

Steps to be taken in case material is released or spilled

SWEEP UP AND REMOVE

Waste Disposal Method

TRANSPORT TO LAND FILL OR SPREAD ON AGRICULTURAL ACREAGE

Precautions to be taken in handling and storing

WEAR DUST MASK IN DUSTING CONDITION

SECTION VIII	CONTROL MEASURES
---------------------	-------------------------

Respiratory Protections (specify)

NOT REQUIRED